

required pursuant to Hazardous Product Regulations 2015

Calcium Modified Silica

Date: 18.03.2025 Page/pages: 1/12 Revision: -

SECTION 1: Identification

Calcium Modified Silica **Product name:**

N0141 **Product code:**

Other means of Inhibisil 33; Inhibisil 73; Inhibisil 75; 8002066; 8011718 identification:

Product type: Powder.

Relevant identified uses of the substance or mixture and uses advised against

Product use: Industrial applications.

Use of the

Additive

substance/mixture:

Uses advised against: Not applicable Manufacturer:

QEMETICA US Silica LLC 3150 Pete Manena Road,

Westlake, LA 70669, USA Customer Service: 1-800-243-6745

QEMETICA NL SIlica B.V.

Valgenweg 1-3, 9936 HV Farmsum

The Netherlands

Postal Adress: P.O. Box 181, 9930AD Delfzijl, The Netherlands

Customer Service: +31-596-676710 Technical Service: +31-596-676710

E-mail address for the person responsible for the safety data sheet:

sds@gemetica.com

Emergency telephone number

+1 703-741-5970 (Chemtrec Emergency number, **Washington DC:**

CCN1020385)

SECTION 2: Hazards identification

Classification of the substance or mixture: Not classified.

GHS label elements:

Signal word: No signal word.

Hazard statements: No known significant effects or critical hazards.

Precautionary statements

Prevention: Not applicable. Not applicable. Response: Not applicable. Storage: Disposal: Not applicable.

Supplemental label

Emits toxic fumes when heated. elements:

SECTION 3: Composition/information on ingredients

Substance/mixture Substance

Product name: Calcium Modified Silica

CAS number/other identifiers



required pursuant to Hazardous Product Regulations 2015

Calcium Modified Silica

Date: 18.03.2025 Revision: - Page/pages: 2/12

CAS number: 1344-95-2

	10 11 10 11			
Ingredient name	Synonyms	% (w/w)	CAS number	
Silicic acid, calcium salt	Calcium silicate; Calcium salt of silicic acid; Calcium monosilicate; Calcium metasilicate; Calcium hydrosilicate; E 552; Calcium polysilicate; calcium silicate non fibrous particles; calcium silicate fibrous particles; Minihole calcium silicate; Calcium silicate, synthetic	80 - 100*	1344-95-2	

^{*}Ranges if listed above for hazardous ingredient(s) are prescribed ranges. The actual concentration(s) or actual concentration range(s) are being withheld as a trade secret.

Contains no detectable crystalline silica (detection limit <0.1% by weight).

SUB codes represent substances without registered CAS Numbers.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section. Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Safety Data Sheet information available. Never give anything by mouth to an unconscious or convulsing person.

Description of necessary first aid measures

Eye contact: Protect the non-irritated eye, remove contact lenses. Rinse

the contaminated eyes carefully with water for 10-15 minutes. Avoid strong streams of water – the risk of damaging the cornea. After rinsing put on an aseptic – sterile

dressing and seek immediate medical advice.

Inhalation: Remove to fresh air. Keep person warm and at rest. If not

breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained

personnel.

Skin contact: Remove contaminated clothing and shoes. Wash skin

thoroughly with soap and water or use recognized skin

cleanser. Do NOT use solvents or thinners.

Ingestion: If swallowed, seek medical advice immediately and show the

packing or label. Keep person warm and at rest. Do NOT

induce vomiting.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact: Exposure to airborne concentrations above statutory or

recommended exposure limits may cause irritation of the

QEMETICA

required pursuant to Hazardous Product Regulations 2015

Calcium Modified Silica

Date: 18.03.2025 Revision: -Page/pages: 3/12

eyes.

Inhalation: Exposure to airborne concentrations above statutory or

recommended exposure limits may cause irritation of the

nose, throat and lungs.

Skin contact: No known significant effects or critical hazards. Ingestion: No known significant effects or critical hazards.

Over-exposure signs/symptoms

Adverse symptoms may include the following: Eye contact:

> irritation redness

Inhalation: Adverse symptoms may include the following:

respiratory tract irritation

coughing

Skin contact: No specific data. **Ingestion:** No specific data.

Indication of immediate medical attention and special treatment needed, if

necessary

Treat symptomatically. Contact poison treatment specialist **Notes to physician:**

immediately if large quantities have been ingested or inhaled.

Specific treatment: No specific treatment

Protection of first-

No action shall be taken involving any personal risk or without aiders:

suitable training.

See toxicological information (Section 11)

SECTION 5: Fire-fighting measures

Extinguishing media

Suitable Use an extinguishing agent suitable for the

extinguishingmedia: surrounding fire.

Unsuitable extinguishing None known.

Specific hazards arising from When transferring material into flammable solvents,

the chemical:

Hazardous thermal decomposition products:

Special protective actions

Promptly isolate the scene by removing all persons

for fire-fighters: from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or

without suitable training.

materials: metal oxide/oxides.

Special protective

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus equipment for fire-fighters:

(SCBA) with a full face-piece operated in positive

use proper grounding to avoid electrical sparks.

Decomposition products may include the following

pressure mode.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

No action shall be taken involving any personal risk or without For non-emergency personnel: suitable training. Evacuate surrounding areas.

QEMETICA

required pursuant to Hazardous Product Regulations 2015

Calcium Modified Silica

Date: 18.03.2025 Revision: -Page/pages: 4/12

> unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing dust. Put on appropriate personal protective equipment.

For emergency responders:

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For

nonemergency personnel".

Environmental precautions

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Move containers from spill area. Vacuum or sweep up material Small spill:

and place in a designated, labeled waste container. Dispose

of via a licensed waste disposal contractor.

Large spill: Move containers from spill area. Approach release from

upwind. Prevent entry into sewers, water courses, basements or confined areas. Vacuum or sweep up material and place in a designated, labeled waste container. Avoid creating dusty conditions and prevent wind dispersal. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste

disposal.

Reference to other

sections

See Section 1 for emergency contact information.

See Section 8 for information on appropriate personal

protective equipment.

See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

Precautions for safe handling

Put on appropriate personal protective equipment (see **Protective** measures: Section 8). Avoid breathing dust.

Special precautions:

When transferring material into flammable solvents, use

proper grounding to avoid electrical sparks.

Advice on general occupational hygiene:

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

Do not store below the following temperature: -30°C (-22°F). Store in accordance with local regulations. Store in original container protected from moisture, direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.



required pursuant to Hazardous Product Regulations 2015

Calcium Modified Silica

Date: 18.03.2025 Revision: - Page/pages: 5/12

SECTION 8: Exposure controls/personal protection

Control parameters

Occupational exosure limits

Ingredient name	Exposure limits	
	CA Alberta Provincial (Canada,	
	6/2018).	
	Skin sensitizer.	
	8 hrs OEL: 10 mg/m ³ 8 hours. Form:	
	Nonfibrous	
	CA Quebec Provincial (Canada,	
Silicic acid, calcium salt	6/2022).	
	TWAEV: 10 mg/m ³ 8 hours. Form: Total	
	dust.	
	CA Saskatchewan Provincial	
	(Canada, 7/2013).	
	STEL: 20 mg/m ³ 15 minutes.	
	TWA: 10 mg/m ³ 8 hours.	

Consult local authorities for acceptable exposure limits.

Recommended monitoring procedures:

Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Appropriate engineering controls:

Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Environmental exposure controls:

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures:

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection:

Safety glasses with side shields.

Skin protection:

Hand protection:

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.



required pursuant to Hazardous Product Regulations 2015

Calcium Modified Silica

Date: 18.03.2025 Revision: -Page/pages: 6/12

Personal protective equipment for the body should be **Body protection:** selected based on the task being performed and the risks

involved and should be approved by a specialist before

handling this product.

Other skin protection: Appropriate footwear and any additional skin protection

measures should be selected based on the task being performed and the risks involved and should be approved by

a specialist before handling this product.

Respiratory protection: Respirator selection must be based on known or anticipated

> exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is

necessary.

SECTION 9: Physical and chemical properties

Appearance:

Physical state: Solid. Color: White. Odor: Odorless. Odor threshold: Not available. 6.5 to 7.5 pH:

Melting point: No melting point was found up to 550 °C (1 022 °F). Not applicable – solid with melting point > 300 °C (572 °F). Boiling point: Flash point: Not applicable. Product does not sustain combustion.

Auto-ignition Not applicable - based on structure the substance is incapable

temperature: of reaction with oxygen/air.

Decomposition Not available. temperature:

Flammability: Not available - based on structure the substance is incapable

of reaction with oxygen/air.

Lower and upper

Not applicable. explosive (flammable)

limits:

Evaporation rate: Not available. Vapor pressure: Not available. Vapor density: Not applicable.

Relative density: 8.35 Density (lbs/gal) Solubility(ies):

Media	Result
cold water	Soluble

Water Solubility at room

temperature:

 $0.01 \, g/l$

Partition coefficient:

Not applicable noctanol/water: Viscosity Not applicable Volatility 0% (w/w)

% Solid. (w/w) 100



required pursuant to Hazardous Product Regulations 2015

Calcium Modified Silica

Date: 18.03.2025 Revision: - Page/pages: 7/12

SECTION 10: Stability and reactivity

Reactivity

No specific test data related to reactivity available for this product or its ingredients.

Chemical stability

The product is stable.

Possibility of hazardous reactions

Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid

High temperature (>800 C) treatment (calcining). Avoid alteration of product properties before use. Calcining (which may result in crystalline formation) or mixing with additives may alter toxicological properties.

Refer to protective measures listed in sections 7 and 8.

Incompatible materials

Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.

Hazardous decomposition products

Depending on conditions, decomposition products may include the following materials: metal oxide/oxides

SECTION 11: Toxicological information

Information on toxicological effects

Acute Toxicity:

Product/ingredient name	Result	Species	Dose	Exposure
Silicic acid, calcium salt	LC50 Inhalation Dusts and mists	Rat	>5 mg/l	4 hours
	LD50 Dermal LD50 Oral	Rabbit Rat	>5000 mg/kg >5000 mg/kg	-

Conclusion/Summary: non-toxic.

Irritation/Corrosion:

Conclusion/Summary

Skin: The substance does not meet the classification criteria. Eyes: The substance does not meet the classification criteria.. Respiratory: The substance does not meet the classification criteria..

Sensitization:

Conclusion/Summary

Skin: The substance does not meet the classification criteria..

Respiratory: The substance does not meet the classification criteria..

Mutagenicity:

Conclusion/Summary: The substance does not meet the classification criteria..



required pursuant to Hazardous Product Regulations 2015

Calcium Modified Silica

Date: 18.03.2025 Revision: - Page/pages: 8/12

Carcinogenicity:

Conclusion/Summary: Unclassifiable as to carcinogenicity in humans...

Reproductive Toxicity:

Conclusion/Summary: The substance does not meet the classification criteria..

Teratogenicity:

Conclusion/Summary: The substance does not meet the classification criteria...

Specific target organ toxicity (single exposure):

Not available.

Specific target organ toxicity (repeated exposure):

Target organs: Contains material which may cause damage to the following organs: upper respiratory tract, eyes, however changes are reversible. The substance does not meet the classification criteria.

Aspiration hazard:

Not applicable - inorganic, solid substance.

Information on the likely routes of exposure

Potential acute health effects

Eye contact: Exposure to airborne concentrations above statutory or

recommended exposure limits may cause irritation of the

eyes.

Inhalation: Exposure to airborne concentrations above statutory or

recommended exposure limits may cause irritation of the

nose, throat and lungs.

Skin contact: No known significant effects or critical hazards Ingestion: No known significant effects or critical hazards

Over-exposure signs/symptoms

Eye contact: Adverse symptoms may include the following:

irritation redness

Inhalation: Adverse symptoms may include the following:

respiratory tract irritation

coughing

Skin contact: No specific data. Ingestion: No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Conclusion/Summary:

There are no data available on the mixture itself. An epidemiological study was conducted which included 165 precipitated silica workers who had been exposed an average time span of 8.6 years. Of these 165 workers, 44 had been exposed for an average of 18 years. No adverse effects were noted in complete medical examinations (including chest roentgenograms) of these workers. Pulmonary function decrements were correlated only with smoking and age but not with the degree or duration of dust exposures. Laboratory studies have also been conducted in small animals via inhalation of levels of precipitated silica dust of up to 126 mg/cu.m. per periods from six months to two years. Although precipitated silica was temporarily deposited in the animals' lungs, most of the deposited material was cleared soon after



required pursuant to Hazardous Product Regulations 2015

Calcium Modified Silica

Date: 18.03.2025 Revision: -Page/pages: 9/12

> the dust exposure ended. The results of all studies performed by, or known to, Qemetica indicate a very low order of pulmonary activity for synthetic precipitated silicas. Qemetica recommends that persons with breathing problems or lung disease should not work in dusty areas unless a physician approves and certifies their fitness to wear respiratory protection. Repeated exposure of the eyes to a low level of dust can produce eye irritation. Repeated or prolonged inhalation of dust may lead to chronic respiratory irritation. Ingestion may cause nausea, diarrhea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from shortterm and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Short term exposure

Potential immediate

effects:

Potential delayed

effects:

See section 4.

See section 4.

Potential chronic health effects

General:

Repeated or prolonged inhalation of dust may lead to chronic respiratory irritation. An epidemiological study was conducted which included 165 precipitated silica workers who had been exposed an average time span of 8.6 years. Of these 165 workers, 44 had been exposed for an average of 18 years. No adverse effects were noted in complete medical examinations

(including chest roentgenograms) of these workers.

Pulmonary function decrements were correlated only with smoking and age but not with the degree or duration of dust exposures. Laboratory studies have also been conducted in small animals via inhalation of levels of precipitated silica dust of up to 126 mg/cu.m. per periods from six months to two years. Although precipitated silica was temporarily deposited in the animals' lungs, most of the deposited material was cleared soon after the dust exposure ended. The results of all studies performed by, or known to, Qemetica indicate a very low order of pulmonary activity for synthetic precipitated silicas. Qemetica recommends that persons with breathing problems or lung disease should not work in dusty areas unless a physician approves and certifies their fitness to wear

respiratory protection.

Carcinogenicity: No known significant effects or critical hazards. Mutagenicity: No known significant effects or critical hazards. Reproductive Toxicity: No known significant effects or critical hazards.



required pursuant to Hazardous Product Regulations 2015

Calcium Modified Silica

Date: 18.03.2025 Revision: - Page/pages: 10/12

SECTION 12: Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
Silicic acid, calcium salt	Acute LC50 >1000 mg/l	Fish	96 hours

Persistence and degradability

Not available.

Bioaccumulative potential

Not available.

Mobility in soil

Soil/water partition coefficient (Koc): Not available.

Other adverse effects (such as hazardous to the ozone layer)

The substance does not contribute to ozone layer depletion.

SECTION 13: Disposal considerations

Disposal methods:

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

SECTION 14: Transport information

	TDG	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-



required pursuant to Hazardous Product Regulations 2015

Calcium Modified Silica

 Date: 18.03.2025
 Revision: Page/pages: 11/12

 Transport hazard class (es)

 Packing group

 Environmental
 No.
 No.
 No.

Marine pollutant
substancesNot applicable.Not applicable.Not applicable.

Additional information:

TDG: None identified. **IMDG:** None identified. **IATA:** None identified.

Special precautions

for user:

hazards

Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk

according

to IMO instruments:

Not applicable.

SECTION 15: Regulatory information

United States

National Inventory List:

Canada inventory (DSL) All components are listed or exempted.

SECTION 16: Other information

Hazardous Material Information System (U.S.A.)

Health: 1 Flammability: 0 Physical hazards: 0

(*) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on MSDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

National Fire Protection Association (U.S.A.)

Date of previous

issue

09.04.2025

Organization that

prepared EHS

the SDS:



required pursuant to Hazardous Product Regulations 2015

Calcium Modified Silica

Date: 18.03.2025 Revision: - Page/pages: 12/12

Key to abbreviations: ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and

Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of

Pollution From Ships, 1973 as modified by the Protocol of 1978.

("Marpol" = marine pollution)

N/A = Not available

SGG = Segregation Group

UN = United Nations

Indicates information that has changed from previously issued version.

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by Qemetica, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.